

# **Safety Data Sheet**

Copyright, 2015 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 30-9920-7
 Version Number:
 2.00

 Issue Date:
 03/11/15
 Supercedes Date:
 07/31/12

## **SECTION 1: Identification**

## 1.1. Product identifier

G152, Metal Polish Medium Tube (22-190B): G15204

#### 1.2. Recommended use and restrictions on use

## Recommended use

Automotive

1.3. Supplier's details

MANUFACTURER: Meguiar's, Inc. DIVISION: Meguiar's

**ADDRESS:** 17991 Mitchell South, Irvine, CA 92614, USA

**Telephone:** 949-752-8000 (Fax: 949-752-5784)

## 1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

## **SECTION 2: Hazard identification**

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

## 2.1. Hazard classification

Skin Corrosion/Irritation: Category 2.

## 2.2. Label elements

Signal word

Warning

#### **Symbols**

Exclamation mark |

Page 1 of 10

## **Pictograms**



#### **Hazard Statements**

Causes skin irritation.

## **Precautionary Statements**

General:

Keep out of reach of children.

## **Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

## **Response:**

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

## 2.3. Hazards not otherwise classified

None.

11% of the mixture consists of ingredients of unknown acute inhalation toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Non-Hazardous Ingredients	Mixture	40 - 70 Trade Secret *
Petroleum Distillates	64742-88-7	10 - 30 Trade Secret *
Aluminum Oxide	1344-28-1	7 - 13 Trade Secret *
White Mineral Oil (Petroleum)	8042-47-5	5 - 10 Trade Secret *
Conditioners	Trade Secret*	< 5 Trade Secret *
Montan-Wax Fatty Acids	68476-03-9	1 - 5 Trade Secret *
Stearic Acid	57-11-4	1 - 5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Page 2 of 10

#### **Eve Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

**Substance** 

Carbon monoxide Carbon dioxide

#### **Condition**

During Combustion During Combustion

## **5.3.** Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## **6.2.** Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcin
Aluminum Oxide	1344-28-1	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
Aluminum Oxide	1344-28-1	CMRG	TWA:1 fiber/cc	
STEARATES	57-11-4	ACGIH	TWA:10 mg/m3	A4: Not class. as human
				carcin
Petroleum Distillates	64742-88-7	CMRG	TWA:100 ppm	
MINERAL OILS,	8042-47-5	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
HIGHLY-REFINED OILS			mg/m3	carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	
White Mineral Oil (Petroleum)	8042-47-5	CMRG	TWA:5 mg/m3;STEL:10	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

## 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

## **Eye/face protection**

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene

Page 4 of 10

## **Respiratory protection**

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Off-white. Hydrocarbon odor.

**Odor threshold** No Data Available

**pH** 8

Melting pointNo Data AvailableBoiling PointNo Data Available

Flash Point Flash point > 93 °C (200 °F)

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data Available

Vapor Density No Data Available

**Density** 1.2 g/ml

Specific Gravity 1.2 [Ref Std: WATER=1]

**Solubility in Water Solubility- non-water**No Data Available
No Data Available

Partition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosity>=100 centipoiseVolatile Organic Compounds14 % weight

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

Page 5 of 10

#### 10.4. Conditions to avoid

Heat

## 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

#### 10.6. Hazardous decomposition products

## **Substance**

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### **Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

#### **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Inhalation-		No data available; calculated ATE > 50 mg/l
	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Petroleum Distillates	Inhalation-		LC50 estimated to be 20 - 50 mg/l
	Vapor		_

Petroleum Distillates	Dermal	Rabbit	LD50 > 3,000 mg/kg
Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-	Rat	LC50 > 2.3 mg/l
	Dust/Mist		
	(4 hours)		
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Stearic Acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Montan-Wax Fatty Acids	Ingestion	Rat	LD50 > 15,000 mg/kg
Stearic Acid	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

## **Skin Corrosion/Irritation**

Name	Species	Value
Petroleum Distillates	Rabbit	Irritant
Aluminum Oxide	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Stearic Acid	Rabbit	Mild irritant

**Serious Eye Damage/Irritation** 

Name	Species	Value
Petroleum Distillates	Rabbit	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Stearic Acid	Professio	Moderate irritant
	nal	
	judgeme	
	nt	

## **Skin Sensitization**

Name	Species	Value
Petroleum Distillates	Guinea	Not sensitizing
	pig	
White Mineral Oil (Petroleum)	Guinea	Not sensitizing
	pig	

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Petroleum Distillates	In vivo	Not mutagenic
Petroleum Distillates	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Aluminum Oxide	In Vitro	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Stearic Acid	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillates	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic

White Mineral Oil (Petroleum)	Inhalation	Multiple animal	Not carcinogenic
		species	
Stearic Acid	Ingestion	Rat	Not carcinogenic

## Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesi s
White Mineral Oil (Petroleum)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not toxic to development	Rat	NOAEL 4,350 mg/kg/day	during gestation

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum Distillates	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
Stearic Acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Petroleum Distillates	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Petroleum Distillates	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Petroleum Distillates	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Petroleum Distillates	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Aluminum Oxide	Inhalation	pneumoconiosis   pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

White Mineral Oil	Ingestion	hematopoietic	Some positive data exist, but the	Rat	NOAEL	90 days
(Petroleum)		system	data are not sufficient for		1,381	
			classification		mg/kg/day	
White Mineral Oil	Ingestion	liver   immune	Some positive data exist, but the	Rat	NOAEL	90 days
(Petroleum)		system	data are not sufficient for		1,336	
			classification		mg/kg/day	
Stearic Acid	Ingestion	blood	Some positive data exist, but the	Rat	NOAEL Not	6 weeks
			data are not sufficient for		available	
			classification			

#### **Aspiration Hazard**

Name	Value
Petroleum Distillates	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

## **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

General Transportation Statement: This product does not require classification by DOT, IATA, ICAO or IMDG.

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact manufacturer for more information

Page 9 of 10

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	% by Wt
Aluminum Oxide	1344-28-1	7 - 13
Aluminum Oxide (ALUMINUM OXIDE	1344-28-1	7 - 13
(FIBROUS FORMS ONLY))		

## 15.2. State Regulations

Contact manufacturer for more information

#### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

## 15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

#### **NFPA Hazard Classification**

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 30-9920-7
 Version Number:
 2.00

 Issue Date:
 03/11/15
 Supercedes Date:
 07/31/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com